

Multi Gas Clip Infrared

The first portable multi gas detector
with a battery life of months instead of hours



- Operates for 2 months continuously on a single charge*
- Detects combustible gases (LEL), hydrogen sulfide (H₂S), carbon monoxide (CO) & oxygen (O₂)
- 1-year calibration cycle* saves test gas & valuable time
- Infrared LEL sensor does not require oxygen to detect gas
- Low maintenance cost
- Infrared LEL sensor is immune to poisons
- Simple one-button operation & large, easy-to-read screen
- Lightweight & durable - alligator clip clamps on tight

Bump testing before each day's use is advised.

*All detectors are charged and calibrated during manufacturing.

gasclip
technologies

Portable Gas Detectors You Can Count On

gascliptech.com • +1.972.775.7577 • Toll-free: 1.877.525.0808

Contact us: <https://www.gascliptech.com/contactus.php>



Multi Gas Clip Version

Multi Gas Clip Infrared Part# MGC	Infrared four gas detector H ₂ S, CO, O ₂ & LEL
---	--

Included with detector: charger, calibration cap, calibration certification & Quick Start Guide

Multi Gas Clip Accessories



Multi Gas Clip Dock*
Part# MGC-DOCK
High Pressure Part# MGC-DOCK-HP

Multi Gas Clip Wall Mount Dock*
Part# MGC-WMDOCK
High Pressure Part# MGC-WMDOCK-HP



Confined Space Kit w/Gas*
Part# GCT-CSK-GAS
Confined Space Kit Without Gas
Part# GCT-CSK



Quad Gas Cylinders
25ppm H₂S, 100ppm CO, 18% O₂ & 50% LEL
58L Part# MGC-Q-58
116L Part# MGC-Q-116



GCT IR Link
Part# GCT-IR-LINK



MGC Vehicle Charger
Part# MGC-CHARGER-V



MGC Multi Charger
Part# MGC-CHARGER-MULTI



Hand Aspirator Kit
Part# GCT-HAK

*Detector(s) not included

Please contact us for additional accessories and spare parts.

Distributed by:

SPECIFICATIONS

Size - Weight	4.7" H x 2.4" W x 1.2" D (118.6 x 61.6 x 31.7 mm) • 7.7 oz. (240 g)
Temperature	-4° to +122°F (-20° to +50°C)
Humidity	5% to 95% RH (non-condensing)
Battery Life	60 days (continuous)
Charge Time	4 - 6 hours
Alarms	Visual, vibrating & audible (minimum 95 dB) Low, High, STEL, TWA & OL (Over Limit)
LEDs	4 Red alarm bar LEDs Yellow back-light (activated on button press) Red back-light (activated on alarm condition) Yellow maintenance notification LED
Display	High viewing angle alphanumeric Liquid Crystal Display (LCD)
Logs	25 Bump tests 25 Events 25 Calibrations Continuous 1-second data logging (typical capacity > 2 months)
Tests	Full-function self-test upon activation Sensors, battery and circuitry tests run continuously
Ratings	EMC Directive 2004/108/EC IP 67

Certifications and Approvals

CSA: CSA13CA0014
Intrinsically Safe/Sécurité Intrinsèque
Class I, Division 1, Group A, B, C and D, T4
Ex ia IIC T4 Ga
Class I, Zone 0, AEx ia IIC T4 Ga
-20°C ≤ Ta ≤ 50°C; 4.2 Vdc
ANSI/ISA 12.13.01-2000
C22.2 No 152 - M1984
C22.2 No 60079-0:11
C22.2 No 60079-11:14

IECEX: IECEX CSA 13.0014
Ex ia IIC Ga
IEC 60079-1:2014-06 Edition: 7.0
-20°C ≤ Ta ≤ 50°C
IEC 60079-0:2017 Edition: 7.0
IEC 60079-11:2011 Edition: 6.0

ATEX: SIRA 14ATEX2013
Ex ia IIC T4 Ga
-20°C ≤ Ta ≤ 50°C
EN IEC 60079-0:2018
EN 60079-11:2012

UKCA: CSAE 22UKEX1230
EX ia IIC T4 Ga
-20°C ≤ Ta ≤ 50°C
EN IEC 60079-0:2018
EN 60079-11:2012

Warranty

Full 2 years

Gases

H ₂ S	0 - 100 ppm (0.1 ppm increments)
CO	0 - 500 ppm (1 ppm increments)
Combustible (LEL)	0 - 100% LEL (0.1% increments)
O ₂	0 - 30% vol. (0.1% increments)

Sensor Type

H₂S, CO & O₂.....Plug-in electrochemical cell
Combustible (LEL)....Plug-in infrared

Recommended Calibration Frequency

1 year



USER OPTIONS

Custom user message	Bump test interval	SAFE display
TWA/STEL intervals	Low/High alarm	Dock lock
Languages (6)	Off-Lock	Calibration gas percentage
Latching alarms	TWA method	Calibration interval
Self-test lock	Sensor enable/disable	TWA/STEL alarm
Auto-zero on start up	Maintenance notification	% LEL or % CH4 by-vol

Specifications are subject to change without notice due to ongoing product development.

Copyright © 2023 Gas Clip Technologies, Inc. All Rights Reserved

MGC v3.17

Service van EURO-INDEX

EURO-INDEX verleent service op alle meetinstrumenten uit haar leveringspakket en biedt de faciliteiten, kennis en hoog gekwalificeerd personeel voor (preventief) onderhoud, reparatie en kalibratie van uw meetinstrumenten.

Geautoriseerd Service Centrum

EURO-INDEX is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum.

Dit betekent dat uw instrumenten worden behandeld door goed opgeleid en kundig personeel, dat beschikt over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen gebruikt en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

Service- en kalibratielaboratorium

EURO-INDEX beschikt over een bijzonder modern service- en kalibratielaboratorium met RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor verschillende grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105.



KWS®

KWS is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie. Veel zaken worden voor u geregeld, zodat u zonder zorgen gebruik kunt maken van uw meetinstrumenten. De kosten zijn laag en voorspelbaar.

Digitale toegang tot uw kalibratiecertificaten met Mijn KWS

Via het Mijn KWS webportal heeft u altijd en overal toegang tot uw kalibratiecertificaten en gerelateerde documenten.

Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Deskundig advies
- Instrumenten worden geleverd met accessoirepakket en herleidbaar kalibratiecertificaat

EURO-INDEX Academy

- Producttrainingen (individueel en klassikaal)
- Seminars
- Demonstratie- en instructievideo's

Bekijk de video op ons YouTube kanaal en ontdek alles over KWS



Servicebalie



Kalibratie rookgasanalyse



Seminars en workshops



Kalibratie thermografie

Wijzigingen voorbehouden EURO-INDEX® VL 18001

Het Bluetooth® woord- en beeldmerk zijn eigendom van Bluetooth SIG, Inc. Gebruik van deze merken door EURO-INDEX geschiedt onder licentie.



BELGIË
Leuvensesteenweg 607
1930 Zaventem
T: 02 - 757 92 44
F: 02 - 757 92 64
info@euro-index.be
www.euro-index.be

NEDERLAND
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: +31 - (0)10 - 2 888 000
F: +31 - (0)10 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl

