

Multi Gas Clip Simple

**Portable 4-gas detector that runs for 2-years
with no need to recharge!**



Gas Detection Made SIMPLE

- Operates for 2 years continuously with no recharging*
- Detects combustible gases (LEL), hydrogen sulfide (H₂S), carbon monoxide (CO) & oxygen (O₂)
- Routine calibrations* not necessary saving test gas & downtime
- Infrared LEL sensor does not require oxygen to detect gas
- Low maintenance cost - infrared LEL sensor is immune to poisons
- Simple one-button operation & large, easy-to-read screen
- Lightweight & durable - alligator clip clamps on tight

Bump testing before each day's use is advised.

*All detectors are charged and calibrated during manufacturing.

gas clip
technologies

Portable Gas Detectors You Can Count On

gascliptech.com • +1.972.775.7577 • Toll-free: 1.877.525.0808

Contact us: <https://www.gascliptech.com/contactus.php>



Multi Gas Clip Simple Version

Multi Gas Clip Simple
Part# MGC-S

Non-charging infrared two
year four gas detector for
H₂S, CO, O₂ & LEL

Included with detector: calibration cap, calibration certificate
& Quick Start Guide

Multi Gas Clip Simple Accessories



MGC Simple Clip Dock*
Part# MGC-S-DOCK
Hi-Pressure Part# MGC-S-DOCK-HP



**MGC Simple Clip Dock
Wall Mount***
Part# MGC-S-WMDOCK
Hi-Pressure Part# MGC-S-WMDOCK-HP



**MGC Simple External Dust
Filter Cap plus 5 Filters**
Part# MGC-S-X-FILTER-KIT
Replacement Filters (Qty. 10)
Part# MGC-S-X-FILTER-10



GCT IR Link
Part# GCT-IR-LINK



MGC Remote Sampling Probe
Part# PROBE-1



Hand Aspirator Kit
Part# GCT-HAK



Quad Gas Cylinders
25ppm H₂S, 100ppm CO, 18% O₂ & 50% LEL
58L Part# MGC-Q-58
116L Part# MGC-Q-116



Confined Space Kit with Gas*
Part# GCT-CSK-GAS
Kit Without Gas Part# GCT-CSK

*Detector(s) not included

Please contact us for additional accessories and spare parts.

Distributed by:

SPECIFICATIONS

| | |
|---------------------|---|
| Size | 4.75" H x 2.75" W x 1.25" D (120.65 x 69.85 x 31.75 mm) |
| Weight | 7.675 oz. (220.2 g) |
| Temperature | -4° to +122°F (-20° to +50°C) |
| Humidity | 5% to 95% RH (non-condensing) |
| Battery Life | 730 days continuous (based on avg. of 1 minute of alarm/day) |
| Alarms | Visual, vibrating & audible (minimum 95 dB) Low, High, STEL, TWA & OL (Over Limit) |
| LEDs | 4 Red alarm bar LEDs Yellow back-light (activated on button press) Red back-light (activated on alarm condition) Yellow maintenance notification LED |
| Display | High viewing angle alphanumeric Liquid Crystal Display (LCD) |
| Logs | 50 bump tests, 50 events, 50 calibrations Continuous 1-second data logging (typical capacity > 2 months) |
| Tests | Full-function self-test upon activation Sensors, battery and circuitry tests run continuously |

Ingress Protection IP 68

Certifications and Approvals



CSA: CSA16.70084100
Intrinsically Safe/Sécurité Intrinsèque
Class I, Division 1, Group A, B, C, and D T4
Ex ia IIC T4 Ga
Class I, Zone 0, AEx ia IIC T4 Ga
-20°C ≤ Ta ≤ +50°C
C22.2 No.152-M1984
ANST/ISA 12.13.01-2000



IECEX: IECEx CSA 16.0038
Ex ia IIC T4 Ga
-20°C ≤ Ta ≤ +50°C
IEC 60079-0:2011 Edition: 6.0
IEC 60079-11:2011 Edition: 6.0



ATEX: SIR4 16ATEX2288
Ex II 1G
Ex ia IIC T4 Ga
EN 60079-0:2012/A11:2013
EN 60079-11:2012

Warranty Full 2 years

| | |
|--------------|---|
| Gases | H ₂ S.....0 - 100 ppm (0.1 ppm increments) |
| | CO.....0 - 500 ppm (1 ppm increments) |
| | Combustible (LEL)0 - 100% LEL (0.1% increments) |
| | O ₂0 - 30% vol. (0.1% increments) |

Sensor Type H₂S, CO & O₂.....Plug-in electrochemical cell
Combustible (LEL)Soldered infrared (IR)

Can Be Calibrated

USER OPTIONS

| | |
|--------------------------|-----------------------------------|
| Custom user message | TWA method |
| TWA/STEL intervals | Sensor enable/disable |
| Languages (6) | SAFE display |
| Latching alarms | Dock lock |
| Self-test lock | Calibration gas concentration |
| Bump test interval | Calibration interval |
| Low/High alarm | TWA/STEL alarm |
| Maintenance notification | % LEL or % CH ₄ by-vol |

Specifications are subject to change without notice due to ongoing product development.

Copyright © 2023 Gas Clip Technologies, Inc. All Rights Reserved

Service van EURO-INDEX

EURO-INDEX verleent service op alle meetinstrumenten uit haar leveringspakket en biedt de faciliteiten, kennis en hoog gekwalificeerd personeel voor (preventief) onderhoud, reparatie en kalibratie van uw meetinstrumenten.

Geautoriseerd Service Centrum

EURO-INDEX is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum.

Dit betekent dat uw instrumenten worden behandeld door goed opgeleid en kundig personeel, dat beschikt over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen gebruikt en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

Service- en kalibratielaboratorium

EURO-INDEX beschikt over een bijzonder modern service- en kalibratielaboratorium met RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor verschillende grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105.



KWS®

KWS is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie. Veel zaken worden voor u geregeld, zodat u zonder zorgen gebruik kunt maken van uw meetinstrumenten. De kosten zijn laag en voorspelbaar.

Digitale toegang tot uw kalibratiecertificaten met Mijn KWS

Via het Mijn KWS webportal heeft u altijd en overal toegang tot uw kalibratiecertificaten en gerelateerde documenten.

Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Deskundig advies
- Instrumenten worden geleverd met accessoirepakket en herleidbaar kalibratiecertificaat

EURO-INDEX Academy

- Producttrainingen (individueel en klassikaal)
- Seminars
- Demonstratie- en instructievideo's

Bekijk de video op ons YouTube kanaal en ontdek alles over KWS



Servicebalie



Kalibratie rookgasanalyse



Seminars en workshops



Kalibratie thermografie

Wijzigingen voorbehouden EURO-INDEX® VL 18001

Het Bluetooth® woord- en beeldmerk zijn eigendom van Bluetooth SIG, Inc. Gebruik van deze merken door EURO-INDEX geschiedt onder licentie.



BELGIË
Leuvensesteenweg 607
1930 Zaventem
T: 02 - 757 92 44
F: 02 - 757 92 64
info@euro-index.be
www.euro-index.be

NEDERLAND
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: +31 - (0)10 - 2 888 000
F: +31 - (0)10 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl

