

Single Gas Clip Plus

Hibernate mode allows it to rest when not in use extending the life of the detector



- **Hibernate Mode - every minute rested is a minute of life saved**
- **Unmatched sensor reliability for H₂S**
- **Adjustable alarm set points & real-time gas reading capability**
- **0.1 ppm resolution for H₂S sensor and display**
- **Two-way IR comms for event downloads, bump tests & updates**
- **Programmable individual detector identification**
- **Simple-to-use one-button operation**
- **“Bump Check” confirmation/identification**
- **No hidden service charges or maintenance fees**
- **Lightweight & durable - clamps on tight with alligator clip**



Portable Gas Detectors You Can Count On
gascliptech.com • +1.972.775.7577 • Toll-free: 1.877.525.0808
Contact us: <https://www.gascliptech.com/contactus.php>



Single Gas Clip Plus Version

Single Gas Clip Plus H₂S

Part# SGC-P-H

Portable gas detector with
Hibernate Mode for
hydrogen sulfide (H₂S)

Included with detector: calibration cap, calibration certificate &
Quick Start Guide

Single Gas Clip Accessories



SGC Dock

Part# SGC-DOCK*

Also available in High Pressure
Part# SGC-DOCK-HP



SGC Wall Mount Dock

Part# SGC-WMDOCK*

Also available in High Pressure
Part# SGC-WMDOCK-HP



GCT IR Link

Part# GCT-IR-LINK



SGC Manual Regulator

Part# REG-MANUAL



58L Gas Cylinders

H₂S - 25 ppm H₂S/N₂
Part# SGC-H2S-58



116L Gas Cylinders

H₂S - 25 ppm H₂S/N₂
Part# SGC-H2S-116

*Detector(s) not included

Please contact us for additional accessories and spare parts.

Distributed by:

SPECIFICATIONS

Size - Weight	3.4 H x 1.9 W x 1.1 D in. (85.5 x 48 x 29 mm.) • 2.7 oz. (76g)
Temperature	-40°C to +50°C/-40°F to +122°F
Humidity	5% to 95% RH (non-condensing)
Battery Life	Two Years
Alarms	Visual, vibrating & audible (minimum 95 dB) Detector life countdown (EOL), Low, High & Over limit (OL)
Display	High viewing angle Alphanumeric Liquid Crystal Display
Logs	25 Events - newer events replace older events
Tests	Full function self-test upon activation and every 20 hours Continuous automatic battery tests

Ratings EMC Directive 2004/108/EC IP 67

Certifications and Approvals



CSA: CSA 16CA70075707
Intrinsically Safe/Sécurité Intrinsèque
Class I, Division 1, Groups A, B, C and D;
T4 EX ia IIC T4 Ga
Class I, Zone 0, AEx ia IIC T4 Ga
-40°C ≤ Ta ≤ +50°C
CAN/CSA-C22.2 No. 60079-0:19
CAN/CSA-C22.2 No. 60079-11:14



IECEx: IECEx CSA 16.0020; Ex ia IIC T4 Ga
-40°C ≤ Ta ≤ +50°C
IEC 60079-0:2017 Edition: 7
IEC 60079-11:2011 Edition: 6



ATEX: SIRA 16ATEX2087; Ex ia IIC T4 Ga
-40°C ≤ Ta ≤ +50°C
EN 60079-0:2018
EN 60079-11:2012



UKCA: CSAE 21UKEX2476; Ex ia IIC T4 Ga
-40°C ≤ Ta ≤ +50°C
EN 60079-0:2018
EN 60079-11:2012

Warranty Full Two Years

Gases H₂S Measuring range: 0-100 ppm
Low alarm limit: 10 ppm - High alarm limit: 15 ppm

*Note: Alarm set points listed above are factory default. These set points can be changed using the GCT IR Link (sold separately).

Sensor Type Plug-in electrochemical cell



USER OPTIONS

Custom user message	Display real-time gas readings or time remaining
Bump due LED	Self-test interval
Bump test interval	Low alarm set point
Calibration gas percentage	High alarm set point
Calibration interval	

Specifications are subject to change without notice due to ongoing product development.
Copyright © 2023 Gas Clip Technologies, Inc. All Rights Reserved

Service van EURO-INDEX

EURO-INDEX verleent service op alle meetinstrumenten uit haar leveringspakket en biedt de faciliteiten, kennis en hoog gekwalificeerd personeel voor (preventief) onderhoud, reparatie en kalibratie van uw meetinstrumenten.

Geautoriseerd Service Centrum

EURO-INDEX is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum.

Dit betekent dat uw instrumenten worden behandeld door goed opgeleid en kundig personeel, dat beschikt over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen gebruikt en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

Service- en kalibratielaboratorium

EURO-INDEX beschikt over een bijzonder modern service- en kalibratielaboratorium met RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor verschillende grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105.



KWS®

KWS is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie. Veel zaken worden voor u geregeld, zodat u zonder zorgen gebruik kunt maken van uw meetinstrumenten. De kosten zijn laag en voorspelbaar.

Digitale toegang tot uw kalibratiecertificaten met Mijn KWS

Via het Mijn KWS webportal heeft u altijd en overal toegang tot uw kalibratiecertificaten en gerelateerde documenten.

Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Deskundig advies
- Instrumenten worden geleverd met accessoirepakket en herleidbaar kalibratiecertificaat

EURO-INDEX Academy

- Producttrainingen (individueel en klassikaal)
- Seminars
- Demonstratie- en instructievideo's

Bekijk de video op ons YouTube kanaal en ontdek alles over KWS



Servicebalie



Kalibratie rookgasanalyse



Seminars en workshops



Kalibratie thermografie

Wijzigingen voorbehouden EURO-INDEX® VL 18001

Het Bluetooth® woord- en beeldmerk zijn eigendom van Bluetooth SIG, Inc. Gebruik van deze merken door EURO-INDEX geschiedt onder licentie.



BELGIË
Leuvensesteenweg 607
1930 Zaventem
T: 02 - 757 92 44
F: 02 - 757 92 64
info@euro-index.be
www.euro-index.be

NEDERLAND
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: +31 - (0)10 - 2 888 000
F: +31 - (0)10 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl

